

		BASIC 2 inch	BASIC 3 ½ inch	Classic 5 inch	Classic 7 inch
UL class		CLASS M	CLASS 1	CLASS 2	CLASS 3
Clear opening	W	36″	36″	36″	36″
	Н	78″	78″	78″	78″
Door thickness		2"	3-1/2"	5″	7"
Overall thickness		14.37″	14.37"	15.75″	17.72″
Standard	W	54.33″	54.33″	54.57"	55″
Architrave	Н	85″	85″	85″	85″
Swing radius	R	41-7/8"	41-7/8″	41-7/8″	41-7/8″

AUTHORISED DEALER





BURGLARY RESISTANCE
BURGLARY RESISTANCE



The YOUNG ANN STANDARD vault door has been tested to and approved under the UL 608 test standard, and achieved a protection rating of M.1.2.3. This rating is a measure of an extremely high resistance to attack. UL 608 is one of the world's hardest and most well known test method for vault doors & modular vault against burglary attacks.

BASIC Vault Door is secured with two UL Listed High Security 4-wheel keyless combination locks,. Full length locking bar. Assuring total top to bottom contact with the doors locking jamb.

Vault Door's lock area is protected by a tempered glass relocker system fully protecting the entire locking mechanism area which activates relockers



Underwriters Laboratory testing UL 608 Listed Class M · 1 · 2 · 3.

# LOCKING

Full length locking bar. Assuring total top to bottom contact with the doors locking jamb. Dual four-wheel combination locks is concealed behind a privacy panel for controlled access by one or more attendants.

## EMERGENCY VENTILATOR

Emergency ventilator. It provides life-saving air, should anyone be confined within the vault.

#### DAY GATE

The standard Grille Gate for ventilation of the room during the day and control when the door is open.

## ALARM MICROSWITH

A heavy duty door micro switch is incorporated into the door for possible connection to the main intruder alarm system as additional protection

# DAY GUARD LOCK

Daytime safety detent lock prevent locking personnel inside the vault under holdup conditions

#### FINISH

All Exposed surfaces of door and vestibule are finished in gleam







